


RapidStrut® DS 5



Product Specifications:

- Used for quick and easy installation
- Unique hole pattern, allowing RapidStrut® accessories to be mounted on both sides of the rail
- Corrosion protection remains intact even after cutting
- Strength equal to US strut 1-5/8" x 1-5/8" x 12 gauge
- Designed with continuous perforation
- Distance between rail end and first hole is always equal
- Continuous graduated centimeter scale on one side
- Surface protection: Product is part of the BIS UltraProtect® 1000 system - withstands a salt spray corrosion test for a minimum of 1,000 hours (maximum 5% red rust) according to ISO 9227
- Suitable for indoor and outdoor applications
- Material: pre-galvanized steel

Item Number	Strut size (inches)	Length (feet)	Items per bundle
65058352	1-5/8 x 2 x 14 g	10	10



PRODUCT SUBMITTAL		Architect / Owner:
Job Name:		
		Contractor:
Date:		
Part No.	Qty:	Notes:

THE INFORMATION CONTAINED IN THIS SUBMITTAL SHEET IS PROPRIETARY TO WALRAVEN, INC. AND IS SUBJECT TO CHANGE WITHOUT NOTICE. THIS INFORMATION MAY NOT BE REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION FROM WALRAVEN, INC. **walraven**