


Walraven Závítové adaptéry (M/F)

přizpůsobení závitových spojů

(K 55 35)



6473XXX



6473521
6484321

Vlastnosti a výhody

- doporučené zatížení pouze v tahu
- pro zvětšení či zmenšení závitu vůči závitu objímky, apod.
- materiál: ocel
- pozinkováno

Výr. č.	H (mm)	h (mm)	G1	G2	Lm1 (mm)	Lm2 (mm)	SW1 (mm)	F _{a,z} (N)	M.Bal.	V.Bal.	Hmot./MJ (g)
6473008	19	12	M8	M6	7,0	5,5	13	2 500	100	1 000	10.00
6473206	20	12	M6	M8	7,0	6,0	13	4 800	100	1 000	15.00
6473210	23	15	M10	M8	9,0	6,0	13	4 800	100	1 000	15.00
6473212	23	15	M12	M8	8,0	6,0	17	4 800	50	500	25.00
6473221	30	22	G1/2	M8	13,0	8,0	27	4 800	50	250	70.00
6473306	21	13	M6	M10	7,0	6,0	13	5 900	100	1 000	15.00
6473308	21	13	M8	M10	7,0	6,0	13	5 900	100	1 000	15.00
6473312	25	15	M12	M10	8,0	8,0	17	5 900	50	500	30.00
6473316	32	22	M16	M10	13,0	8,0	24	5 900	25	250	70.00
6473321	31	21	G1/2	M10	12,0	8,0	27	5 900	25	250	73.00
6473408	23	13	M8	M12	7,0	7,5	13	8 800	50	1 000	18.00
6473410	23	13	M10	M12	8,0	7,5	13	8 800	50	1 000	15.00
6473416	32	22	M16	M12	11,0	8,0	24	8 800	50	250	75.00
6473510	32	18	M10	M16	9,0	11,0	19	10 800	50	250	55.00
6473512	32	18	M12	M16	10,0	11,0	19	19 900	50	250	50.00
6473421	26	11	M10	G1/2	9,0	13,0	27	10 800	25	125	80.00
6473521	15	-	M16	G1/2	15,0	-	-	19 900	100	1 000	14.00
6473621	25	15	G3/4	G1/2	12,0	7,0	-	12 700	25	250	70.00
6473721	32	20	G1	G1/2	17,0	9,0	-	5 500	10	100	100.00

