

Rubber Lined Split Clamp

15 - 318 mm

(A 05 184)



Features and benefits

- lock bolts with combi cross recessed head
- for horizontal and vertical applications
- profiled for extra strength
- screws secured with anti-loss washer
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- temperature resistance from -20 °C to +110 °C
- noise insulating lining, rubber, black
- noise reduction up to 18dB (A)

Part No.	D (mm)	D (")	DN	G	B (mm)	H (mm)	h (mm)	b x s (mm)	F _{a,z} (N)	Pack 1
DMC215018	15 - 19	3/8	15	M8	60	36	26	19 x 1.2	1,500	450
DMC215022	20 - 25	1/2	22	M8	65	43	29	19 x 1.2	1,500	400
DMC215028	36 - 30	3/4	28	M8	70	50	32	19 x 1.2	1,500	350
DMC215035	32 - 36	1	35	M8	85	56	36	19 x 1.2	1,500	300
DMC215040	38 - 43	1 1/4	42	M8	92	63	39	19 x 1.2	1,500	250
DMC215048	47 - 51	1 1/2	48	M8	98	72	42	19 x 1.2	1,500	200
DMC215054	53 - 58	-	54	M8	104	75	45	19 x 1.2	1,500	200
DMC215060	60 - 64	2	60	M8	110	81	48	19 x 1.2	1,500	125
DMC215063	36 - 66	-	63	M8	115	88	51	19 x 1.2	1,500	125
DMC215070	68 - 72	-	70	M8	120	91	53	19 x 1.2	1,500	125
DMC215075	74 - 80	2 1/2	75	M8/10	125	96	56	19 x 1.5	2,000	100
DMC215083	81 - 86	-	83	M8/10	139	108	60	19 x 1.5	2,000	100
DMC215090	87 - 92	3	90	M8/10	146	111	63	19 x 1.5	2,000	100
DMC215100	99 - 105	3 1/2	100	M8/10	156	121	68	19 x 1.5	2,000	75
DMC215110	107 - 112	-	110	M8/10	166	131	73	19 x 1.5	2,000	75
DMC215115	113 - 118	4	115	M8/10	171	136	76	19 x 1.5	2,000	70
DMC215125	125 - 130	-	125	M8/10	181	146	81	19 x 2.0	2,000	70
DMC215133	131 - 137	-	133	M8/10	184	154	85	19 x 2.0	2,000	50
DMC215140	138 - 142	5	140	M8/10	196	161	88	19 x 2.0	2,000	50
DMC215150	148 - 153	-	150	M8/10	206	171	93	19 x 2.0	2,000	50
DMC215160	159 - 166	-	160	M8/10	216	181	98	19 x 2.0	2,000	50
DMC215168	168 - 172	6	168	M8/10	224	189	102	19 x 2.0	2,000	50
DMC215200	200 - 212	-	200	M8/10	256	221	118	19 x 2.0	3,000	50
DMC215220	215 - 220	8	220	M8/10	276	241	128	19 x 2.0	3,000	40
DMC215250	249	-	250	M8/10	306	271	143	19 x 2.0	3,000	40
DMC215315	313 - 318	-	315	M8/10	371	336	176	19 x 2.0	3,000	25

Hot Dip Galvanized and Stainless Steel option available on request.

With connection nut M8/M10, M10/M12 available on request.

With M6 Side Nuts available on request.

These series replaces part number DMC115 series.

