

Rubber Lined Two Bolt Clamp

(A 12 310)



Features and benefits

- designed to act as a horizontal support for heavier pipes
- two bolt arrangement provides sturdier support
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- temperature resistance from -20 °C to +110 °C
- noise insulating lining, rubber, black
- noise reduction up to 18dB (A)
- designed to meet MSS Standard SP-58-2002, type 4 and SP-69

Part No.	D (")	Bolt	b x s (mm)	k (mm)	F _{a,z} (N)	Pack 1
DMC212022	1/2	M10	25 x 5.0	200	1,700	60
DMC212028	3/4	M10	25 x 5.0	210	1,700	60
DMC212035	1	M10	25 x 5.0	230	1,700	50
DMC212040	1 1/4	M10	25 x 5.0	260	1,700	50
DMC212048	1 1/2	M10	25 x 5.0	260	1,700	40
DMC212060	2	M10	25 x 5.0	260	1,700	35
DMC212075	2 1/2	M12	25 x 6.0	290	4,000	35
DMC212090	3	M12	25 x 6.0	290	4,000	30
DMC212100	3 1/2	M12	25 x 6.0	300	4,000	30
DMC212115	4	M12	25 x 6.0	330	4,000	25
DMC212140	4	M16	40 x 6.0	350	6,000	20
DMC212168	6	M16	40 x 6.0	380	6,000	15
DMC212220	8	M16	40 x 9.0	470	11,000	10
DMC212273	10	M16	50 x 9.0	520	12,000	5
DMC212323	12	M20	50 x 12.0	580	15,000	4
DMC212355	14	M20	50 x 12.0	610	15,000	4
DMC212406	16	M20	60 x 16.0	660	22,000	2
DMC212457	18	M20	60 x 16.0	710	22,000	2
DMC212508	20	M20	60 x 16.0	760	22,000	1
DMC212610	24	M20	60 x 16.0	880	22,000	1

Hot Dip Galvanized and Stainless Steel option available on request.

