

Rubber Support Insert – 75 mm

(D 15 340)

21.3 – 609.6 mm



Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
 - 1/2" to 2": 25 mm
 - 2" to 5": 38 mm
 - 6" and above: 50 mm
 - non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 – 1,400 kg/m³
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI127525	21.3	1/2	15	-	-	Steel Pipe	50
DMRSI347525	26.7	3/4	20	-	-	Steel Pipe	40
DMRSI17525	33.4	1	25	-	-	Steel Pipe	35
DMRSI1147525	42.1	1 1/4	32	-	-	Steel Pipe	30
DMRSI1127525	48.2	1 1/2	40	-	-	Steel Pipe	30
DMRSI27525	60.3	2	50	-	-	Steel Pipe	25
DMRSI2127538	73.0	2 1/2	65	-	-	Steel Pipe	15
DMRSI37538	88.9	3	80	-	-	Copper Pipe	15
DMRSI3127538	101.6	3 1/2	90	-	-	Steel Pipe	12
DMRSI47538	114.3	4	100	-	-	Steel Pipe	12
DMRSI57538	141.3	5	125	-	-	Steel Pipe	12
DMRSI67550	168.3	6	150	-	-	Steel Pipe	10
DMRSI87550	219.1	8	200	-	-	Steel Pipe	100
DMRSI107550	273.0	10	250	-	-	Steel Pipe	80
DMRSI127550	323.8	12	300	-	-	Steel Pipe	70
DMRSI147550	355.6	14	350	-	-	Steel Pipe	70
DMRSI167550	406.4	16	400	-	-	Steel Pipe	50
DMRSI187550	457.2	18	450	-	-	Steel Pipe	30
DMRSI207550	508.0	20	500	-	-	Steel Pipe	30
DMRSI247550	609.6	24	600	-	-	Steel Pipe	20

Self extinguishing rubber inserts available on request.