

Two Bolt Clamp

(B 14 315)



Features and benefits

- designed to act as a horizontal support for heavier pipes
- two bolt arrangement provides sturdier support
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- designed to meet MSS Standard SP-58-2002, type 4 and SP-69

Part No.	D (")	Bolt	b x s (mm)	k (mm)	F _{a,z} (N)	Pack 1
DMC211022	1/2	M10	25 x 5.0	200	1,700	60
DMC211028	3/4	M10	25 x 5.0	210	1,700	60
DMC211035	1	M10	25 x 5.0	230	1,700	50
DMC211040	1 1/4	M10	25 x 5.0	260	1,700	50
DMC211048	1 1/2	M10	25 x 5.0	260	1,700	40
DMC211060	2	M10	25 x 5.0	260	1,700	35
DMC211075	2 1/2	M12	25 x 6.0	290	4,000	35
DMC211090	3	M12	25 x 6.0	290	4,000	30
DMC211100	3 1/2	M12	25 x 6.0	330	4,000	30
DMC211115	4	M12	25 x 6.0	330	4,000	25
DMC211140	5	M16	40 x 6.0	350	6,000	20
DMC211168	6	M16	40 x 6.0	380	6,000	15
DMC211220	8	M20	40 x 9.0	470	11,000	10
DMC211273	10	M16	50 x 9.0	520	12,000	5
DMC211323	12	M20	50 x 12.0	580	15,000	4
DMC211355	14	M20	50 x 12.0	610	15,000	4
DMC211406	16	M20	60 x 16.0	660	22,000	2
DMC211457	18	M20	60 x 16.0	710	22,000	1
DMC211508	20	M20	60 x 16.0	760	22,000	1
DMC211610	24	M20	60 x 16.0	880	22,000	1

Hot Dip Galvanized and Stainless Steel option available on request.

