

Pacifyre® A Acrylic Fire Sealant


(U 04 100)



Features and Benefits

- up to EI 240 for linear gap seals
- up to EI 120 for pipe penetration
- up to EI 90 for cable penetration
- single insulated metal pipes up to DN200
- multiple insulated metal pipes up to DN80
- cable bundles up to Ø 50 mm (max. Ø 21 mm each cable)
- for sealing annular joints around pipes, fire collars and fire sleeves or wraps
- remains elastic after curing
- colour fast, waterproof and paintable after curing
- shrinkage approx. 15% (DIN 52451)
- indoor emission level A+
- temperature resistance from -20 °C to +80 °C
- application temperature: +5 °C up to +30 °C
- sound reduction up to 62dB
- pipe and cable penetrations: CE marked ETA 22/0037
- linear gap seals: CE marked ETA 16/1008
- tested according to EN 1366-3, EN 1366-4 and EN ISO 717-1

- for more information, please refer to the Declaration of Performance / ETA, www.walraven.com/pacifyre



Part No.	Colour	Certification	Cont.	Pack 1
2180100010	White	ETA	300 ml	12

Complementary

Pacifyre® MK II Fire Sleeve (P)
Pacifyre® EFC Fire Collar
Pacifyre® BFC

Complementary

Pacifyre® ID-Card
Tangit 2C Pistol PP6
WIS Dispenser Gun