

WCP Cavity Plug


(L 07 25)

metal anchor with screw for cavity walls



Features and Benefits

- high load capacity and security
- usable with various screwdriver bit types
- Application:
 - shelves
 - wall-mounted cabinets
 - sanitary fixings
 - HVAC and plumbing fixings
- material: steel
- zinc plated
- substrate type:
 - hollow masonry
 - chipboard
 - plasterboard



Part No.	Code	L	d ₀	d _{s,m}	h _{min,max}	t _{fix,max}	Drive	Rec. Tension Load Vertically Perforated Brick (Hz 12) (kN)	Rec. Tension Load Chipboard (h=13mm) (kN)	Rec. Tension Load Plasterboard d (h=12.5m m) (kN)	Rec. Tension Load Cement Fiberboard (h=12mm) (kN)	Pack 1	Pack 2
6105400	WCP 4x35	35 mm	8	M4	4 - 9	16	Philips	-	0.20	0.15	0.35	100	1,200
6105501	WCP 5x37	37 mm	10	M5	5 - 13	20	Philips	-	0.25	0.18	0.40	100	1,200
6105502	WCP 5x50	50 mm	10	M5	5 - 18	26	Philips	-	0.25	0.18	0.40	100	900
6105601	WCP 6x37	37 mm	12	M6	4 - 13	16	Philips	0.70	0.28	0.20	0.42	100	900
6105603	WCP 6x63	63 mm	12	M6	16 - 32	28	Philips	0.70	0.28	0.20	0.42	100	300

Given recommended loads include a safety factor of 3.