
## Walraven Pacifyre® FPC Fire Collar

for fire resistant sealing of plastic and multi-layer pipes 50 - 160 mm

(U 04 02)



## Features and Benefits

- for application in flexible walls, rigid walls built-in sound insulation and rigid floors
- suitable for combustible pipes with intended use as rainwater, sewage, gas, drinking water and heating or cooling
- for various combustible pipe materials such as PP-H, PVC and PE
- suited for certain branded pipes
- easy to install due to the connection
- possible to mount 1 half and connect other half later
- collar stays in place by itself in vertical situations because of Foam layer
- with a fire resistance up to EI 120 U/U

| Part No.   | D    | d    | Model         | В     | Н    | Pack 1 |
|------------|------|------|---------------|-------|------|--------|
|            | (mm) | (mm) |               | (mm)  | (mm) |        |
| 2122000050 | 50   | 58   | 2 fixing tabs | 148.5 | 30   | 1      |
| 2122000063 | 63   | 71   | 4 fixing tabs | 129.1 | 30   | 1      |
| 2122000075 | 75   | 83   | 4 fixing tabs | 146.8 | 40   | 1      |
| 2122000090 | 90   | 98   | 4 fixing tabs | 156.8 | 40   | 1      |
| 2122000110 | 110  | 118  | 4 fixing tabs | 175.5 | 40   | 1      |
| 2122000125 | 125  | 133  | 4 fixing tabs | 169.1 | 60   | 1      |
| 2122000140 | 140  | 148  | 6 fixing tabs | 259.0 | 60   | 1      |
| 2122000160 | 160  | 168  | 6 fixing tabs | 284.0 | 60   | 1      |

tested according to EN 1366-3

■ European approval: ETA-22/0341





