

U-Strap Clamp

(B 17 305)



Features and Benefits

- for mounting plain or insulated pipes
- can be used with Rubber Support Inserts
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- designed to meet MSS Standard SP-58, type 26 and SP-69

Part No.	D (")	Bolt	B (mm)	b x s (mm)	k (mm)	F _{a,z} (N)	Pack 1
WMC155022	1/2	M8	76	25 x 2.0	51	5,500	500
WMC155028	3/4	M8	82	25 x 2.0	57	5,500	400
WMC155035	1	M8	89	25 x 2.0	64	5,500	400
WMC155040	1 1/4	M8	96	25 x 2.0	71	5,500	350
WMC155048	1 1/2	M8	102	25 x 2.0	77	5,500	300
WMC155054	-	M8	108	25 x 2.0	83	5,500	250
WMC155060	2	M8	114	25 x 2.0	89	5,500	200
WMC155067	-	M8	121	25 x 2.0	96	5,500	200
WMC155075	2 1/2	M8	145	25 x 3.0	113	6,500	150
WMC155082	-	M8	152	25 x 3.0	120	6,500	150
WMC155090	3	M8	160	25 x 3.0	128	6,500	150
WMC155100	3 1/2	M8	170	25 x 3.0	138	6,500	150
WMC155108	-	M8	178	25 x 3.0	146	6,500	125
WMC155115	4	M8	185	25 x 3.0	153	6,500	125
WMC155126	-	M10	196	25 x 3.0	164	6,500	125
WMC155140	5	M10	210	25 x 3.0	178	6,500	100
WMC155148	-	M10	218	28 x 3.0	186	6,500	100
WMC155155	-	M10	225	25 x 3.0	193	6,500	100
WMC155168	6	M10	237	25 x 3.0	205	6,500	100
WMC155179	-	M10	249	25 x 3.0	217	6,500	100
WMC155190	-	M10	260	38 x 3.0	228	9,000	50
WMC155205	-	M10	275	38 x 3.0	243	9,000	50
WMC155219	8	M10	289	38 x 3.0	257	9,000	50
WMC155230	-	M10	300	38 x 3.0	268	9,000	30

Other dimensions available on request.
Hot Dip Galvanized and Stainless Steel option available on request.

