

U-Strap Clamp

(B 17 310)



Features and Benefits

- for mounting plain or insulated pipes
- can be used with Rubber Support Inserts
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- designed to meet MSS Standard SP-58, type 26 and SP-69

Part No.	D (")	Bolt	B (mm)	b x s (mm)	k (mm)	F _{a,z} (N)	Pack 1
WMC155241	-	M12	332	38 x 4.0	291	13,500	35
WMC155263	-	M12	354	38 x 4.0	313	13,500	35
WMC155273	10	M18	364	38 x 4.0	323	13,500	35
WMC155295	-	M18	386	38 x 4.0	345	13,500	30
WMC155323	12	M18	414	38 x 4.0	373	13,500	30
WMC155356	14	M18	447	50 x 4.0	406	19,000	10
WMC155374	-	M18	465	50 x 4.0	424	19,000	15
WMC155406	16	M18	497	50 x 4.0	456	19,000	15
WMC155432	-	M18	523	50 x 4.0	482	19,000	15
WMC155456	18	M18	547	50 x 4.0	506	19,000	10
WMC155482	-	M18	573	50 x 4.0	532	19,000	10
WMC155508	20	M18	599	50 x 4.0	558	19,000	10
WMC155533	-	M18	624	50 x 4.0	583	19,000	10
WMC155559	-	M18	650	50 x 4.0	609	19,000	10
WMC155583	-	M18	674	50 x 4.0	633	19,000	10
WMC155610	24	M18	701	50 x 4.0	660	19,000	10
WMC155658	-	M18	766	50 x 6.0	718	24,000	5
WMC155690	-	M18	198	50 x 6.0	750	24,000	5
WMC155760	-	M18	868	50 x 6.0	820	24,000	5
WMC155863	-	M18	971	50 x 6.0	923	24,000	5
WMC155918	-	M18	1,026	50 x 6.0	978	24,000	5

Other dimensions available on request.
Hot Dip Galvanized and Stainless Steel option available on request.

