

WPF Plasterboard Fixings

(L 07 22)

A classic hammer-in fixing for plasterboard



61100XX

61102XX

Features and Benefits

- quick and easy to install
- central thread guide provides optimum screw positioning
- does not require drilling
- sharp tip allows precise installation
- for use with $\varnothing$ 3.5-5.0 mm wood or chipboard screws
- Application:
 - interior decorations
 - pictures
 - lamps
 - electrical fittings
- material: steel
- zinc plated
- substrate type:
 - plasterboard

Part No.	Code	Model	L	$l_{s,min}$	$d_{s,w}$	l_s	h_{max}	$t_{fix,max}$	Drive	Rec. Tension Load Plasterboard ($h=1$ 2.5m m) (kN)	Pack 1	Pack 2
				(mm)	(mm)	(mm)	(mm)	(mm)				
6110063	WPF 12x30	Screw excluded	30 mm	27	3.5 - 5.0	-	12.5	-	-	0.102*	200	4,800
6110092	WPF 12x30	Screw excluded	30 mm	27	3.5 - 5.0	-	12.5	-	-	0.102*	3,000	-
6110262	WPF 12x30 / 4x30	Screw included	30 mm	27	4.0	30	12.5	3	PZ2	0.102*	200	4,800
6110263	WPF 12x30 / 4x50	Screw included	30 mm	27	4.0	50	12.5	3	PZ2	0.102*	200	4,800
6110334	WPF 12x30 / 4x50	Screw included	30 mm	27	4.0	50	12.5	23	PZ2	0.102*	25	3,750

* Recommended loads are for tension, have been reached using a 4.0 mm diameter wood screw and include a safety factor of 2.

