

WUP Uni Plug

(L 07 07)

standard universal anchor for all types of substrates



Features and Benefits

- high load capacity
- can be used with wood screws, chipboard screws and metric bolts
- suitable for variety of substrates
- easily slides into holes
- does not slip past collar in deep holes
- does not expand prematurely
- resists rotation in holes
- Application:
 - shelves
 - wall-mounted cabinets
 - sanitary fixings
 - HVAC and plumbing fixings
- material: high quality PA6 polyamide
- substrate type:
 - lightweight concrete
 - concrete
 - masonry
 - hollow masonry
 - rock
 - sand-lime bricks
 - natural stone
 - gypsum

Part No.	Cod e	L	l _{s,min}	d ₀	h ₀	d _{s,w}	d _{s,m}	Rec. Tens ion Load Solid Brick	Rec. Tens ion Load Perforat ed Brick	Rec. Tens ion Load C20/ 25 Conc rete	Rec. Tens ion Load Ligh twei ght Conc rete	Rec. Tens ion Load Sand stone	Pack 1	Pack 2
			(mm)	(mm)	(mm)	(mm)	(mm)	(kN)	(kN)	(kN)	(kN)	(kN)		
61007208	WUP 8x40	40 mm	44	8	50	4.5 - 6.0	-	1.00	0.40	1.15	0.19	1.00	300	3,600
61007210	WUP 10x50	50 mm	54	10	70	6.0 - 8.0	-	1.10	0.45	1.90	0.30	1.80	150	1,800
61007212	WUP 12x60	60 mm	64	12	70	8.0 - 10.0	-	1.50	0.50	2.70	0.40	2.10	100	1,200

Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 5.

