

# Walraven RapidRail® Stainless Steel Fixing Rail

(M 20 05)

suspension and support



6507001

6507015

6507002

## Features and Benefits

- C-profile
- for a quick and easy fixing
- with continuous perforation
- distance between rail end and first hole is always equal
- a continuous graduated centimetre scale on one side
- material: stainless steel 1.4404 (AISI 316L)

Part No.	Type	L	B (mm)	H (mm)	s (mm)	S (mm)	RAL	BndS	BndL
6507001	30x15	2 m	30	15	2.00	15	-	20	480
6507015	30x20	2 m	30	20	1.75	15	-	20	480
6507002	30x30	2 m	30	30	2.00	15	RAL <sup>1</sup>	20	400


*RAL<sup>1</sup> = tested, certified and monitored by a third party according to RAL-GZ 655/C.*

*For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.*

*For more information about the max. allowed load ( $F_{0,2}$ ) please refer to the loading tables or our online datasheet 'Technical Details BIS RapidRail®'.*



RAL-GZ 655/C  
Cert.Nr. 2012-07



## Complementary

Walraven RapidRail® Stainless Steel Slide  
Nut  
Walraven RapidRail® Stainless Steel  
Hammerfix