

# Walraven RapidStrut® Ball Swivel Hanger


fixing to Strut rail

(H 24 75)





## Features and Benefits

- slide nut with ball swivel hanger, washer and BIS RapidStrut® spring
- recommended for metal pipes up to DN 50, plastic pipes up to DN 100
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- with inspection hole to check screw-in depth (attention: when the threaded rod is screwed-in too deep, the ball swivel is blocked)
- screw-in depth is continuously variable (see LU)
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated
- tested for fire safety according to EN 1363-1



Part No.	G	L	LU (mm)	s (mm)	Lm1 (mm)	SW1 (mm)	SW2 (mm)	For Rail	F <sub>a,z</sub> (N)	Pack 1
66530805	M8	80 mm	43	6.0	50	13	10	Strut	3,100	25
66530005	M10	80 mm	43	8.0	50	13	12	Strut	3,100	25

Please note. Always use 2 ball swivel hangers and secure by additional hexagon nut (see application picture). The maximum length change that can be dealt with, depends on the fixing distance (ceiling - pipe). The height difference that occurs as a result, needs to be taken into consideration. To be used in combination with BIS Ball Swivel Hangers. Product can be found on page E 10 05.



## Complementary

BIS Ball Swivel Hanger  
Walraven RapidStrut® Cantilever Arm  
(BUP1000)  
Walraven RapidStrut® Channel DS 5  
(BUP1000)