

Walraven RapidStrut® Stainless Steel Channel

(M 45 05)

suspension and support




6507X27

6507X47

Features and Benefits

- universal rail system
- distance between rail end and first hole is always equal
- a continuous graduated centimetre scale on one side
- inward formed flanges with serrated profile for extra grip
- Walraven RapidStrut® channels 41x41x2.5 tested for fire safety according to EN 1363-1
- for more information about the max. allowed load ( $F_{a,2}$ ) please refer to the loading tables or our online datasheet 'Walraven RapidStrut® Data Sheet'
- material: stainless steel 1.4404 (AISI 316L)

| Part No. | L   | B<br>(mm) | H<br>(mm) | s<br>(mm) | S<br>(mm) | Pack 1 | BndS | BndL |
|----------|-----|-----------|-----------|-----------|-----------|--------|------|------|
| 6507327  | 3 m | 41        | 21        | 2.50      | 22        | 3      | 150  | -    |
| 6507627  | 6 m | 41        | 21        | 2.50      | 22        | 6      | 300  | -    |
| 6507347  | 3 m | 41        | 41        | 2.50      | 22        | 3      | 150  | -    |
| 6507647  | 6 m | 41        | 41        | 2.50      | 22        | 6      | 60   | 300  |



Complementary

Walraven RapidStrut® Stainless Steel Slide Nut G2  
Walraven RapidStrut® Stainless Steel Slide Nut with Tabs  
RIS Strut Stainless Steel Tee-Bolt

Complementary

Walraven RapidStrut® Stainless Steel Base Plate G2