

Walraven Wall Mounting Set 62 H + Support

(H 19 25)

universal Mounting Set for outdoor appliances



Features and Benefits

- suitable for indoor and outdoor use
- universal mounting brackets for fixing indoor and outdoor appliances to the wall
- designed for the most common standard heat pumps (for heat pump models with female thread, Walraven Wall Mounting set consists of: ISO Kit 6901998 needs to be ordered separately - see assembly instruction)
- stepless adjustable in height and wall
- with anti-vibration mounts type Walraven VibraTek® SB-MM

- material: steel 1.0332
- material: vibration damper; rubber SBR + NR 55°+-5 Shore A steel class 4.8
- surface treatment: hot dip galvanized (EN-ISO 1461)
- - 2 Cantilever Arms type RapidStrut 62 H with welded support
 - 2 lengths of 500mm wall rail type RapidStrut 62|H
 - 4 vibration dampers with preassembled fasteners
 - 6 rail endcaps
 - fasteners to connect Cantilever Arms to the wall rail
 - assembly instruction
 - anchors for mounting to the wall not included (order seperately)

Part No.	Туре	L	L1	Н	h	$F_{a,z}$	Pack 1	App.
			(mm)	(mm)	(mm)	(N)		
6901990	62 H + Support	970 mm	900	808	400	1,750	1	pc.
Max. allowed load $F_{a,z}$ per Set: 1.750 Newton (Total weight of the unit).								
wax. allowed 1000 $r_{0,z}$ per Set: 1.750 Newton (10tal Weight of the unit).								



