walraven

BIS Pipe Reinforcement Scale

support for plastic pipe \emptyset 16 to 200 mm and \emptyset 1/2" to 3"

(K 35 07)





Features and benefits

- self-gripping and continuous support for plastic pipes to prevent unsatisfactory deflections
- allows for longer distance between supports
- controls direction of pipe expansion.
 Maintains alignment of pipe, and prohibits "snaking"
- reinforcement fits inside insulation. Maintains "plenum rating"
- lightweight and economical, also 10 foot lengths are easy to handle
- eases handling and speeds installation of plastic pipes
- can be cut with hand tools
- material: steel
- pre-galvanized
- complimentary product: works well with BISMAT® 5000

| Part No. | D | D / CTS | D / IPS | L | Recommended hanger spacing | BndS |
|----------|------|---------|---------|------|----------------------------|------|
| | (mm) | (") | (") | | (ft) | |
| PSU050-9 | | 1/2 | - | 9 ft | 5 | 50 |
| PSU075-9 | | 3/4 | 1/2 | 9 ft | 5 | 50 |
| PSU100-9 | | 1 | 3/4 | 9 ft | 6 | 50 |
| PSU125-9 | | 1-1/4 | 1 | 9 ft | 7 | 50 |
| PSU150-9 | | 1-1/2 | 1-1/4 | 9 ft | 8 | 50 |
| PSU200-9 | | 2 | - | 9 ft | 8 | 50 |
| PRM020 | 20 | - | 3/8 | 3 m | 5 | 50 |
| PRM025 | 25 | - | - | 3 m | 6 | 50 |
| PRM032 | 32 | - | - | 3 m | 7 | 50 |
| PRM040 | 40 | - | - | 3 m | 8 | 50 |
| PRM050 | 50 | - | 1-1/2 | 3 m | 8 | 50 |
| PRM063 | 63 | - | 2 | 3 m | 8 | 50 |
| PRM075 | 75 | - | 2-1/2 | 3 m | 8 | 50 |
| PRM090 | 90 | - | 3 | 3 m | 8 | 50 |
| PRM110 | 110 | - | 4 | 3 m | 8 | 50 |
| PRM125 | 125 | - | 4 | 3 m | 8 | 50 |
| PRM160 | 160 | - | - | 3 m | 8 | 50 |
| PRM200 | 200 | - | - | 3 m | 8 | 50 |
| PRM315 | 315 | - | - | 3 m | 8 | - |

