

BIS Nagibno tiplo (Ravni navoj)

fixing to hollow walls & ceilings

(L 10 25)




0670602



0670603
0670604
0670614

Prednosti i osobine

- U-profil sa pregibnim navojnim štiftom za pričvršćivanje
- za pričvršćivanje na šuplje zidove, stropove, knauf ploče, profilirani krov, itd
- Art.br. 0670604: za pričvršćivanje sprinkler instalacija na čelične ploče (max. dimenzije do DN 50 - 2") po propisu skladnom normi VdS
- load capacity of the plug is influenced by the surface
- materijal: metalni dijelovi čelik; (Art.br. 0670604 sa zaštitnim gumenim prstenom)
- elektrizom cinkovan
- VdS-norma - sertifikat br. G 4890027
- with FM-approval - certificate number 3047342 max. DN 40 - 1 1/2"

Cert.Nr.
G 4890027

067 0 602

067 0 603 /
067 0 604 /
067 0 614

Art.br.	Model	G	L	B (mm)	H0 (mm)	SW1 (mm)	FM	VdS	KK
0670602	Ravni navoj	M6	100 mm	68,5	17	10	-	-	100
0670603	Ravni navoj	M8	100 mm	74,0	20	13	-	-	50
0670604	Ravni navoj	M10	100 mm	84,0	25	17	FM	VdS	25

Part No. 0670604: breaking load is 20 kN.

Naznačene vrijednosti dozvoljenog opterećenja su ovisni od nosive podloge gdje se proizvod montira (npr. opterećenje trapezoidne ploče se određuje po m²).