



BISOFIX® PIR30 + HD500

(D 03 66)

za rashladne medije 76,1 - 323,9 mm

**Prednosti i osobine**

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- ne sadrži FCKW, HFCKW, formaldehid ili kadmium supstance
- otpornost na požar klasa: B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- zaštita materijala:
 - proizvod je deo Walraven BIS UltraProtect® sistema
 - pogodan za unutrašnju i spoljašnju upotrebu
 - izdržava min. 1 000 sati sonog sprej testa (max. 5% crvene rdje) prema ISO standardu 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Art.br.	D (mm)	Model	F _{a,z} (N)	KK
I303304076	76,1	BISOFIX® PIR30 + HD500 Clamp	460	25
I303304089	88,9	BISOFIX® PIR30 + HD500 Clamp	500	15
I303304102	101,6	BISOFIX® PIR30 + HD500 Clamp	550	15
I303304108	108,0	BISOFIX® PIR30 + HD500 Clamp	620	15
I303304114	114,3	BISOFIX® PIR30 + HD500 Clamp	1.370	15
I303304133	133,0	BISOFIX® PIR30 + HD500 Clamp	1.520	5
I303304140	139,7	BISOFIX® PIR30 + HD500 Clamp	1.570	5
I303304160	159,0 - 160,0	BISOFIX® PIR30 + HD500 Clamp	1.720	5
I303304168	168,3	BISOFIX® PIR30 + HD500 Clamp	2.720	2
I303304219	219,1	BISOFIX® PIR30 + HD500 Clamp	4.210	2
I303304273	273,1	BISOFIX® PIR30 + HD500 Clamp	5.020	2
I303304324	323,9	BISOFIX® PIR30 + HD500 Clamp	5.790	2