



BISOFIX® PIR50 + 2S

(D 03 82)

za rashladne medije 12,0 - 114,3 mm

**Prednosti i osobine**

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- ne sadrži FCKW, HFCKW, formaldehid ili kadmij supstance
- otpornost na požar klasa: B2
- PIR density for D < 110mm = 80kg/m³
- PIR density for D > 110mm = 120kg/m³
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- obujmica elektrolizom cinkovana
- temperature range -45 °C - +105 °C

Art.br.	D (mm)	Model	F _{a,z} (N)	KK
I503303012	12,0	BISOFIX® PIR50 + 2S Clamp	220	25
I503303015	15,0 - 16,0	BISOFIX® PIR50 + 2S Clamp	250	25
I503303018	17,2 - 18,0	BISOFIX® PIR50 + 2S Clamp	300	25
I503303028	26,9 - 28,0	BISOFIX® PIR50 + 2S Clamp	350	25
I503303034	33,7 - 35,0	BISOFIX® PIR50 + 2S Clamp	370	25
I503303042	42,4	BISOFIX® PIR50 + 2S Clamp	470	25
I503303048	48,3	BISOFIX® PIR50 + 2S Clamp	500	15
I503303054	54,0	BISOFIX® PIR50 + 2S Clamp	520	15
I503303057	56,0 - 57,0	BISOFIX® PIR50 + 2S Clamp	520	15
I503303060	60,3	BISOFIX® PIR50 + 2S Clamp	540	15
I503303064	64,0	BISOFIX® PIR50 + 2S Clamp	550	15
I503303070	70,0	BISOFIX® PIR50 + 2S Clamp	600	15
I503303076	76,1	BISOFIX® PIR50 + 2S Clamp	650	15
I503303089	88,9	BISOFIX® PIR50 + 2S Clamp	690	15
I503303102	101,6	BISOFIX® PIR50 + 2S Clamp	720	5
I503303108	108,0	BISOFIX® PIR50 + 2S Clamp	760	5
I503303114	114,3	BISOFIX® PIR50 + 2S Clamp	1.680	5