



BISOFIX® PIR50 + HD500

(D 03 86)

za rashladne medije 76,1 - 406,4 mm



Prednosti i osobine

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- ne sadrži FCKW, HFCKW, formaldehid ili kadmium supstance
- otpornost na požar klasa: B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- zaštita materijala:
 - proizvod je deo Walraven BIS UltraProtect® sistema
 - pogodan za unutrašnju i spoljašnju upotrebu
 - izdržava min. 1 000 sati sonog sprej testa (max. 5% crvene rdje) prema ISO standardu 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Art.br.	D (mm)	Model	F _{a,z} (N)	KK
I503304076	76,1	BISOFIX® PIR50 + HD500 Clamp	650	15
I503304089	88,9	BISOFIX® PIR50 + HD500 Clamp	690	15
I503304102	101,6	BISOFIX® PIR50 + HD500 Clamp	720	5
I503304108	108,0	BISOFIX® PIR50 + HD500 Clamp	760	5
I503304114	114,3	BISOFIX® PIR50 + HD500 Clamp	1.680	5
I503304133	133,0	BISOFIX® PIR50 + HD500 Clamp	2.780	2
I503304140	139,7	BISOFIX® PIR50 + HD500 Clamp	2.860	2
I503304160	159,0 - 160,0	BISOFIX® PIR50 + HD500 Clamp	3.090	2
I503304168	168,3	BISOFIX® PIR50 + HD500 Clamp	3.200	2
I503304219	219,1	BISOFIX® PIR50 + HD500 Clamp	4.810	2
I503304273	273,1	BISOFIX® PIR50 + HD500 Clamp	5.620	2
I503304324	323,9	BISOFIX® PIR50 + HD500 Clamp	6.390	2
I503304406	406,4	BISOFIX® E13 + HD500 Clamp	6.410	2