

WNP Nail Plug

easy to install hammer-set anchor

(L 07 18)



Prednosti i osobine

- quick and easy to install
- pre-assembled
- long expansion zone provides stability
- can be adjusted or dismantled
- materijal: čelik
- material: high quality PA6 plyamide
- elektrizom cinkovan
- substrate type:
 - concrete
 - masonry
 - rock
 - stone
 - sand-lime bricks
 - natural stone

Art.br.	Kode	L	d _s	d ₀	h ₀	l _s	h _{nom,min}	t _{fix,max}	Drive	Rec. Load Brick (kN)	KK	VP
62232604	WNP 6x40	40 mm	4 (mm)	6 (mm)	40 (mm)	40 (mm)	30 (mm)	10 (mm)	PZ2	0,20	200	2.400
62232606	WNP 6x60	60 mm	4 (mm)	6 (mm)	40 (mm)	60 (mm)	30 (mm)	20 (mm)	PZ2	0,20	200	2.400
62232806	WNP 8x60	60 mm	4 (mm)	8 (mm)	50 (mm)	60 (mm)	40 (mm)	20 (mm)	PZ2	0,45	100	-
62232808	WNP 8x80	80 mm	4 (mm)	8 (mm)	50 (mm)	80 (mm)	40 (mm)	40 (mm)	PZ2	0,45	100	-
62232810	WNP 8x100	100 mm	4 (mm)	8 (mm)	50 (mm)	100 (mm)	40 (mm)	60 (mm)	PZ2	0,45	100	-

Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 2.

