

WUP Uni Plug

standard universal anchor for all types of substrates

(L 07 07)



Prednosti i osobine

- high load capacity
- can be used with wood screws, chipboard screws and metric bolts
- suitable for variety of substrates
- easily slides into holes
- collar prevents the plug from sliding into deeper holes
- does not expand prematurely
- resists rotation in holes
- Application:
 - shelves
 - wall-mounted cabinets
 - sanitary fixings
 - HVAC and plumbing fixings
- material: high quality PA6 plyamide
- substrate type:
 - lightweight concrete
 - concrete
 - masonry
 - hollow masonry
 - rock
 - sand-lime bricks
 - natural stone
 - gypsum

Art.br.	Kod e	L	$l_{s,min}$	d_0	h_0	$d_{s,w}$	$d_{s,m}$	Rec. Load Brick	Rec. Load Perforated Brick	Rec. Load C20/25 Concrete	Rec. Load Lightweight Concrete	Rec. Load Sandstone	KK	VP
			(mm)	(mm)	(mm)	(mm)	(mm)	(kN)	(kN)	(kN)	(kN)	(kN)		
61007206	WUP 6x30	30 mm	34	6	40	3,5 - 5,0	M4		0,20	0,45	0,12	0,70	500	6.000
61007208	WUP 8x40	40 mm	44	8	50	4,5 - 6,0	-	1,00	0,40	1,15	0,19	1,00	300	3.600
61007212	WUP 12x60	60 mm	64	12	70	8,0 - 10,0	-	1,50	0,50	2,70	0,40	2,10	100	1.200

Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 5.

