


Walraven Onderlegring – Vlak

bevestiging aan Walraven RapidRail®


(G 30 75)



Voordelen en kenmerken

- geschikt voor rail 27x18, 30x15, 30x20, 30x30, 30x45, 38x40
- getest op brandveiligheid
- materiaal: staal
- elektrolytisch verzinkt

Art.nr.	B (mm)	s (mm)	d1 (mm)	Voor rail	VPE 1	VPE 2
6533306	25	2,5	Ø 6,4	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	100	1.000
6533308	25	2,5	Ø 8,4	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	100	1.000
6533310	25	2,5	Ø 10,5	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	100	1.000
6533312	25	2,5	Ø 13,0	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	100	1.000
6533316	30	3,0	Ø 17,0	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	100	2.500
Getest op brandveiligheid.						
Art.nr. 6533306 niet getest op brandveiligheid.						



Complementair

Walraven RapidRail® Wandconsole
Walraven RapidRail® Montagerail