

BIS U-Obejmy STN

dla rur $\varnothing 1/4 - 12''$ (13,5 - 323,9 mm)

(M 12 05)



Zalety i właściwości

- U-kształtne obejmy z gwintem
- materiał: stal nierdzewna 1.4401 (AISI 316)
- podkładki i nakrętki w komplecie

Nr kat.	D (mm)	D (")	DN	G	H (mm)	Lm1 (mm)	k (mm)	Pud.
2084706021	21,5	1/2	15	M6	55	25	30	100
2084708027	26,9	3/4	20	M8	59	25	35	100
2084708034	33,7	1	25	M8	70	35	47	100
2084708042	42,4	1 1/4	32	M8	75	35	51	100
2084708049	48,3	1 1/2	40	M8	85	35	60	25
2084708060	60,3	2	50	M8	99	35	71	25
2084708076	76,1	2 1/2	65	M8	121	42	93	25
2084710090	88,9	3	80	M10	126	35	99	25
2084710114	114,3	4	100	M10	159	50	123	25
2084712140	139,7	5	125	M12	191	50	152	25
2084716219	219,1	8	200	M16	280	60	236	10
2084716273	273,0	10	250	M16	340	55	305	10
2084718323	323,9	12	300	M18	388	60	350	10

