

# Walraven Suport Strut

fixare pe perete

(H 12 50)




6658 3 801



6658 3 802

## Caracteristici și beneficii

- instalare rapidă
- ideal for fastening RapidStrut® Fixing Rails as traverses in shafts or racks
- suitable for rails type 21, 41 or 21 Double
- with pre-assembled screws M10x16mm / SW17 and washers 10,5x40mm
- galvanizat electrolitic
- material: oțel 1.0332



| Art.Nr.  | Model     | L      | B  | H   | s   | s1  | d1      | k  | T <sub>(inst.)</sub> | F <sub>a,y</sub> | F <sub>a,y2</sub> | F <sub>a,x</sub> | F <sub>a,x 2</sub> | Amb. 1 |
|----------|-----------|--------|----|-----|-----|-----|---------|----|----------------------|------------------|-------------------|------------------|--------------------|--------|
| 66583801 | Orizontal | 104 mm | 40 | 120 | 5,0 | 4,0 | 19 x 13 | 80 | 15,0                 | 4.280*           | 9.880*            | 1.760*           | 1.980*             | 25     |
| 66583802 | Vertical  | 104 mm | 40 | 120 | 5,0 | 4,0 | 19 x 13 | 80 | 15,0                 | 4.280*           | 9.880*            | 1.760*           | 1.980*             | 25     |

\*F<sub>a,y</sub> and F<sub>a,x</sub> fixed on rail type L (1,5mm thickness) with M12 and 25Nm.

\*\*F<sub>a,y2</sub> and F<sub>a,x2</sub> fixed on rail type H (2,5mm thickness) with M12 and 35Nm.

