

## BIS U-strmene (Nerez – SSt)

(M 12 05)

pre potrubie Ø ¼ - 12" (13,5 - 323,9 mm)



## Vlastnosti a výhody

- U-strmeň so závitom
- vrátane matic a podložiek
- materiál: nerezová oceľ 1.4401 (AISI 316)

| Výr. č.    | D<br>(mm) | D<br>(") | DN  | G   | H<br>(mm) | Lm1<br>(mm) | k<br>(mm) | M.Bal. | Hmot./MJ<br>(g) |
|------------|-----------|----------|-----|-----|-----------|-------------|-----------|--------|-----------------|
| 2084706021 | 21,5      | ½        | 15  | M6  | 55        | 25          | 30        | 100    | 50.00           |
| 2084708027 | 26,9      | ¾        | 20  | M8  | 59        | 25          | 35        | 100    | 69.00           |
| 2084708034 | 33,7      | 1        | 25  | M8  | 70        | 35          | 47        | 100    | 85.00           |
| 2084708042 | 42,4      | 1¼       | 32  | M8  | 75        | 35          | 51        | 100    | 92.00           |
| 2084708049 | 48,3      | 1½       | 40  | M8  | 85        | 35          | 60        | 25     | 118.00          |
| 2084708060 | 60,3      | 2        | 50  | M8  | 99        | 35          | 71        | 25     | 81.00           |
| 2084708076 | 76,1      | 2½       | 65  | M8  | 121       | 42          | 93        | 25     | 220.00          |
| 2084710090 | 88,9      | 3        | 80  | M10 | 126       | 35          | 99        | 25     | 246.00          |
| 2084710114 | 114,3     | 4        | 100 | M10 | 159       | 50          | 123       | 25     | 326.00          |
| 2084712140 | 139,7     | 5        | 125 | M12 | 191       | 50          | 152       | 25     | 625.00          |
| 2084716219 | 219,1     | 8        | 200 | M16 | 280       | 60          | 236       | 10     | 1470.00         |
| 2084716273 | 273,0     | 10       | 250 | M16 | 340       | 55          | 305       | 10     | 1770.00         |
| 2084718323 | 323,9     | 12       | 300 | M18 | 388       | 60          | 350       | 10     | 2110.00         |

