walraven

WVSF200 Part A

Date of compilation: 30/05/2023 Version: 1

1.1	Product identifier: WVSF200 Part A
	Other means of identification:
1.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Adhesive for construction
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
	J. van Walraven Holding B.V.
	Industrieweg 5 3641 RK Mijdrecht - The Netherlands
	Phone: 0031 297 23 30 00 - Fax: 0031 297 23 30 33
	Info.nl@walraven.com
	www.walraven.com

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

This product contains less than 1% respirable crystalline silica, so it does not require classification

GB CLP Regulation:

Classification of this product has been carried out in accordance with GB CLP Regulation.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

GB CLP Regulation:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Supplementary information:

Contains Methacrylic acid, monoester with propane-1,2-diol, Triphenylphosphine.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

- CONTINUED ON NEXT PAGE -



Date of compilation: 30/05/2023 Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Mixture composed of additives, pigments and resins

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	27813-02-1	Methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	5 - <10 %
CAS:	25013-15-4	Vinyltoluene Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	5 - <10 %
CAS:	603-35-0	Triphenylphosphine Acute Tox. 4: H302; Skin Sens. 1: H317; STOT RE 2: H373 - Warning	0.1 - <0.5 %
To ob	tain more informat	tion on the hazards of the substances consult sections 11, 12 and 16.	1

To obtain more information on the nazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 **Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eve contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 **Extinguishing media:**

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Advice for firefighters: 5.3



Date of compilation: 30/05/2023 Version: 1

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...). **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

Reference to other sections:

See sections 8 and 13.

6.4

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:



Date of compilation: 30/05/2023 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the workplace:

Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Methacrylic acid, monoester with propane-1,2-diol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 27813-02-1	Dermal	Non-applicable	Non-applicable	4.2 mg/kg	Non-applicable
EC: 248-666-3	Inhalation	Non-applicable	Non-applicable	14.7 mg/m ³	Non-applicable
Triphenylphosphine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 603-35-0	Dermal	Non-applicable	Non-applicable	0.07 mg/kg	Non-applicable
EC: 210-036-0	Inhalation	Non-applicable	Non-applicable	0.5 mg/m ³	Non-applicable

DNEL (General population):

		Short	Short exposure		exposure
Identification		Systemic	Local	Systemic	Local
Methacrylic acid, monoester with propane-1,2-diol	Oral	Non-applicable	Non-applicable	2.5 mg/kg	Non-applicable
CAS: 27813-02-1	Dermal	Non-applicable	Non-applicable	2.5 mg/kg	Non-applicable
EC: 248-666-3	Inhalation	Non-applicable	Non-applicable	8.8 mg/m ³	Non-applicable
Triphenylphosphine	Oral	Non-applicable	Non-applicable	0.01 mg/kg	Non-applicable
CAS: 603-35-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 210-036-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

PNEC:

Identification				
Methacrylic acid, monoester with propane-1,2-diol	STP	10 mg/L	Fresh water	0.904 mg/L
CAS: 27813-02-1	Soil	0.727 mg/kg	Marine water	0.904 mg/L
EC: 248-666-3	Intermittent	0.972 mg/L	Sediment (Fresh water)	6.28 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	6.28 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

	Pictogram	PPE	Remarks
	Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
C	Specific protectior	n for the hands	
	Distances and		Descentor

Pictogram	PPE	Remarks
Mandatory hand	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.3 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Date of compilation: 30/05/2023 Version: 1

Pictogram	PPE		Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		according to the manufacturer 's instruct is a risk of splashing.
E Body protection			
Pictogram	PPE	l	Remarks
	Work clothing	to the product for professional/in accordance with the regulations in EN	rioration. For periods of prolonged expo- idustrial users CE III is recommended, ir NISO 6529:2013, EN ISO 6530:2005, EN 13, EN 464:1994.
	Anti-slip work shoes	to the product for professional/ir	rioration. For periods of prolonged expos Idustrial users CE III is recommended, in n EN ISO 20345:2012 y EN 13832-1:200
F Additional emerge	ncy measures		
Emergency meas	sure Standards	Emergency measure	Standards
Emergency show	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:20 wer	011 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
In accordance with the pr	e community legislation for the protect oduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable	information see subsection 7.1.D)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A	e community legislation for the protecti roduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES	information see subsection 7.1.D and Vehicle Refinishing Proc)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bas	e community legislation for the protecti roduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable	information see subsection 7.1.D and Vehicle Refinishing Proc)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bas	e community legislation for the protecti roduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie	information see subsection 7.1.D and Vehicle Refinishing Proc)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A Information on bas For complete informat	e community legislation for the protecti roduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet.	information see subsection 7.1.D and Vehicle Refinishing Proc)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bas For complete informat Appearance:	e community legislation for the protecti roduct and its container. For additional i c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet.	information see subsection 7.1.D and Vehicle Refinishing Proc s:)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet.	information see subsection 7.1.D and Vehicle Refinishing Proc s: s:)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bas For complete informat Appearance: Physical state at 20 °C Appearance:	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie cion see the product datasheet. C: Solic Past Creat	information see subsection 7.1.D and Vehicle Refinishing Proc s: s:)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C Appearance: Colour:	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C Appearance: Colour: Odour:	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am natic)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold:	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie cion see the product datasheet. C: Solid Past Creat Aror Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am natic)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility:	e community legislation for the protecti oduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am natic -applicable *)
In accordance with the spillage of both the pr The Volatile Organie V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A Information on bass For complete informate Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost	e community legislation for the protection oduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical properties tion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non 0 °C: Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d se am natic -applicable * -applicable *)
In accordance with the spillage of both the pr The Volatile Organie V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informate Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 20	e community legislation for the protection oduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie cion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non 0 °C: Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d s: am matic -applicable * -applicable * -applicable *)
In accordance with the spillage of both the pr The Volatile Organie V.O.C. (Supply): V.O.C. density at 2 TON 9: PHYSICAL A Information on bass For complete informate Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 20 Vapour pressure at 50	e community legislation for the protecti roduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non 0 °C: Non 0 °C: Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am matic -applicable * -applicable * -applicable * -applicable *)
In accordance with the spillage of both the pr The Volatile Organi V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informat Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 20 Evaporation rate at 20	e community legislation for the protection oduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non 0 °C: Non 0 °C: Non 1 °C: Non	information see subsection 7.1.D and Vehicle Refinishing Proc s: d e am matic -applicable * -applicable * -applicable * -applicable *)
In accordance with the spillage of both the pr The Volatile Organie V.O.C. (Supply): V.O.C. density at 2 ION 9: PHYSICAL A Information on bass For complete informate Appearance: Physical state at 20 °C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 20 Vapour pressure at 20 Evaporation rate at 20 Product description	e community legislation for the protecti oduct and its container. For additional is c Compounds in Paints, Varnishes 14.22 % weight 20 °C: Non-applicable ND CHEMICAL PROPERTIES ic physical and chemical propertie tion see the product datasheet. C: Solid Past Creat Aror Non pheric pressure: Non 0 °C: Non 0 °C: Non 0 °C: Non	information see subsection 7.1.0 and Vehicle Refinishing Proc s: d s: am matic -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *)

- CONTINUED ON NEXT PAGE -

walraven

WVSF200 Part A

Date of compilation: 30/05/2023 Version: 1

SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	ES (continued)
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	>20.5 mm²/s
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non-applicable
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	355 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Explosive (Solid):	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable *
).2	Other information:	
	Information with regard to physical hazard cla	isses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing info	ormation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

- CONTINUED ON NEXT PAGE -



Date of compilation: 30/05/2023 Version: 1

SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Vinyltoluene (3); Titanium dioxide (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:



Date of compilation: 30/05/2023 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Non-applicable

Specific toxicology information on the substances:

Identification	tification Acute toxicity		Genus
Methacrylic acid, monoester with propane-1,2-diol	LD50 oral	11200 mg/kg	Rat
CAS: 27813-02-1	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Vinyltoluene	LD50 oral	>5000 mg/kg	Rat
CAS: 25013-15-4	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	1.5 mg/L (ATEi)	
Triphenylphosphine	LD50 oral	700 mg/kg	Rat
CAS: 603-35-0	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus	
Methacrylic acid, monoester with propane-1,2-diol	LC50	833 mg/L (96 h)	Scophthalmus maximus	Fish	
CAS: 27813-02-1	EC50	210 mg/L (48 h)	Acartia tonsa	Crustacean	
	EC50	Non-applicable			
Vinyltoluene	LC50	7.6 mg/L (96 h)	Salmo gairdneri	Fish	
CAS: 25013-15-4	EC50	1.3 mg/L (48 h)	Daphnia magna	Crustacean	
	EC50	2.6 mg/L (72 h)	Selenastrum capricornutum	Algae	

Chronic toxicity:

Identification		Concentration	Species	Genus
Methacrylic acid, monoester with propane-1,2-diol	NOEC	Non-applicable		
CAS: 27813-02-1	NOEC	45.2 mg/L	Daphnia magna	Crustacean
Vinyltoluene	NOEC	1.16 mg/L	N/A	Fish
CAS: 25013-15-4	NOEC	0.32 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	De	gradability	Biodegrada	oility
Methacrylic acid, monoester with propane-1,2-diol	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 27813-02-1	COD	Non-applicable	Period	Non-applicable
	BOD5/COD	Non-applicable	% Biodegradable	81 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Methacrylic acid, monoester with propane-1,2-diol	BCF	3
CAS: 27813-02-1	Pow Log	0.97
	Potential	Low
Vinyltoluene	BCF	5
CAS: 25013-15-4	Pow Log	3.44
	Potential	Low
Mobility in soil:		



Date of compilation: 30/05/2023 Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Identification Absorption/desorption		Volatility	
Methacrylic acid, monoester with propane-1,2-diol	Кос	80	Henry	9E-4 Pa·m ³ /mol
CAS: 27813-02-1	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Vinyltoluene	Кос	Non-applicable	Henry	Non-applicable
CAS: 25013-15-4	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.2E-2 N/m (20 °C)	Moist soil	Non-applicable
Triphenylphosphine	Кос	Non-applicable	Henry	Non-applicable
CAS: 603-35-0	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1.168E-2 N/m (408.05 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances		Dangerous

Type of waste:

HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable

- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.' Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:



Date of compilation: 30/05/2023 Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

Classification procedure:

Eve Irrit. 2: Calculation method Skin Sens. 1: Calculation method Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information canno be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.