# **WRX Plastic Plug**

# Plastic self-drilling anchor

WRX PP 14x32



VRX PP 14X32

## **Features and Benefits**

Self-drilling

- Back twist lock allows screw removal without movement of the plug
- Sharp tip allows accurate positioning and installation
- Material: high quality PA6 polyamide, zinc plated steel

#### Suitable base materials

#### **Typical Applications**

Plasterboard

- Interior decorations
- Electrical fittings

#### **Product Details**

Article	Description	Diameter	Length	
		d [mm]	L [mm]	
6229904	WRX PP 14x32	14	32	


#### **Packaging Details**

Article	Description	Pack 1		Pack 2	
		[pcs]	EAN13	[pcs]	EAN13
6229904	WRX PP 14x32	100	8712993273218	2400	8712993277001




# **Setting Details**


Anchor Size			14x32
Anchor length	L	[mm]	32
Screw diameter wood /chipboard	d <sub>s,w</sub>	[mm]	4.5
Screw length	ls	[mm]	30
Drive		[-]	PZ2
Minimum substrate thickness	$h_{min}$	[mm]	12.5



## Installation Instructions







#### Loading Data

Loading data is presented for single anchors.

#### **Characteristic loads**

Anchor Size			14x32
Plasterboard (h=12.5mm)	N <sub>rk</sub>	[kN]	0.27

#### **Recommended loads**

Anchor Size			14x32
Plasterboard (h=12.5mm)	N <sub>rec</sub>	[kN]	0.09

Given recommended tension loads include a safety factor of 3.

